

# CDI

## SAILMAKER'S INFORMATION for FLEXIBLE FURLERS

Revised 9/06

Unit	Luff Deduct	Luff Tape	Min. Tack Height	A	B	C	D	E	F	G	H	I	J	K
FF1	13.0	#6	6.0	1.3	4.5	9.0	3.5	7.0	1.3	2.5	2.0	2.0	7.8	17.5
FF2	13.0	#6	6.0	1.3	4.5	11.0	4.0	7.0	1.3	2.5	2.0	2.0	9.0	18.7
FF4	22.0	#6	9.0	1.5	6.0	13.5	5.7	9.0	2.7	4.7	4.0	2.1	10.5	20.2
FF6	22.0	#6	9.0	1.5	6.0	13.5	5.7	9.0	2.7	4.7	4.0	2.1	10.5	20.2
FF7	27.0	#6	11.0	2.4	7.3	19.7	6.8	13.0	2.7	4.7	7.0	2.1	16.5	27.0
FF9	27.0	#6	11.0	2.9	8.0	19.7	6.8	13.0	3.3	5.5	7.0	2.7	17.0	27.0

### Notes:

Dimensions A-E depend on the length of the toggle at the bottom of the turnbuckle. Dimensions shown assume Merriman (now MacWhyte) turnbuckle.

Dimension H is approximate. The length required may be greater to provide adequate clearance for a Spinnaker halyard, or may be slightly shorter to accommodate a full hoist sail.

Dim H is intended to provide adequate clearance to allow headstay adjustments without the furler binding at the top.

Dim H is also necessary to provide clearance between the mast and the halyard top fitting.

